



US006557671B1

(12) **United States Patent**
Kirimoto et al.

(10) Patent No.: **US 6,557,671 B1**
 (45) Date of Patent: **May 6, 2003**

(54) **CABLE DISC BRAKE**

(75) Inventors: **Kanji Kirimoto, Kaizuka; Tsuyoshi Sakashita, Koube, both of (JP)**

(73) Assignee: **Shimano, Inc., Osaka (JP)**

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/531,570**

(22) Filed: **Mar. 20, 2000**

(51) Int. Cl.⁷ **B62L 3/02**

(52) U.S. Cl. **188/26; 188/72.7**

(58) Field of Search **188/26, 72.7**

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,765,511 A	*	10/1973	Toyomasu	188/26
3,789,959 A		2/1974	Kawaguchi	
3,878,921 A	*	4/1975	Kibler et al	188/26
3,920,102 A		11/1975	Ito	
3,949,838 A		4/1976	Fuhrman	188/26
3,989,124 A		11/1976	Fujii	188/26
4,022,299 A		5/1977	Haraikawa	
4,162,720 A		7/1979	Haraikawa	
4,170,369 A		10/1979	Strutman	280/261
4,284,176 A		8/1981	Haraikawa et al.	
4,454,933 A		6/1984	Hunnicut et al.	
4,633,978 A		1/1987	Hoff	
5,082,092 A		1/1992	Yoshigai	
5,201,402 A		4/1993	Mott	
5,358,078 A		10/1994	Gajek et al.	188/72.4
5,390,771 A		2/1995	Hinkens et al.	188/344

5,960,914 A	10/1999	Isai	
5,979,609 A	* 11/1999	Tsai	188/26
6,206,144 B1	3/2001	Di Bella	

FOREIGN PATENT DOCUMENTS

EP	0 791 531 A2	8/1997
JP	4894132	12/1973

* cited by examiner

Primary Examiner—Matthew C. Graham

(74) Attorney, Agent, or Firm—Shinju Global IP Counselors, LLP

(57) **ABSTRACT**

A bicycle cable disc brake is provided with a cam assembly that has improved efficiency during movement under high pressure. Basically, the cable disc brake has a cable housing, a pair of friction members and an actuated mechanism. The first friction member is movably coupled to the caliper housing between a release position and a braking position. The second caliper is also coupled to the caliper housing and arranged substantially parallel to the first friction member to form a rotor receiving slot therebetween. The actuated mechanism is movably coupled to the caliper housing to move the first friction member from the release position towards the second friction member to the braking position. The actuated mechanism has a pair of cam members movably arranged between an axially retracted position and an axially extended position with a guide member interconnecting the cam members during movement between the axial retracted position and the axially extended position. In the preferred embodiment, the guide member is a guide pin that extends from one of the cam members and is received in a bore of the other cam member.

36 Claims, 18 Drawing Sheets

